

# LED CANDLE

WQJ+14648

LED source LED CANDLE 1 W with E-14 base and in the shape of a glass 'candle'. It is extremely economical to operate - their power output is 1 W. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. It shines with a very warm light (1800K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 300° ensures even illumination of the room.



|                 |                     |                           |               |
|-----------------|---------------------|---------------------------|---------------|
| Power           | <b>1 W</b>          | Voltage                   | <b>230 V</b>  |
| Luminous flux** | <b>60 lm (360°)</b> | Colour temperature        | <b>1800 K</b> |
| Colour of light | <b>WW</b>           | Beam angle                | <b>300 °</b>  |
| Socket          | <b>E14</b>          | Degree of protection (IP) | <b>IP20</b>   |

## Technical data

---

|                              |              |
|------------------------------|--------------|
| Code                         | WOJ+14548    |
| Power                        | 1 W          |
| Nominal current              | 5 mA         |
| Voltage                      | 230 V        |
| Energy consumption           | 1 kWh/1000h  |
| Frequency                    | 50HZ Hz      |
| Power factor                 | 1            |
| Useful luminous flux*        | 60 lm (360°) |
| Luminous flux**              | 60 lm (360°) |
| Lamp efficacy                | 60 lm/W      |
| Colour temperature           | 1800 K       |
| Colour of light              | WW           |
| Beam angle                   | 300 °        |
| RA                           | 80           |
| Uniformity of color SDCM max | 5            |
| Dimmable                     | No           |
| Working temperature range    | +40/-20 °    |
| Lifespan                     | 17000 h      |
| Socket                       | E14          |
| Degree of protection (IP)    | IP20         |
| Dimension (AxBxC)            | 35x98 mm     |
| Made in                      | PRC          |

## Related documents

---



 Declaration of Conformity

