

# LED CANDLE

W0J+14649

LED source LED CANDLE 4 W with E-14 base and in the shape of a glass 'candle'. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. It shines with a very warm light (1800K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 300° ensures even illumination of the room.



|                 |                      |                           |               |
|-----------------|----------------------|---------------------------|---------------|
| Power           | <b>4 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux** | <b>340 lm (360°)</b> | Colour temperature        | <b>1800 K</b> |
| Colour of light | <b>WW</b>            | Beam angle                | <b>300 °</b>  |
| Socket          | <b>E14</b>           | Degree of protection (IP) | <b>IP20</b>   |

## Technical data

---

|                              |               |
|------------------------------|---------------|
| Code                         | W0J+14549     |
| Power                        | 4 W           |
| Nominal current              | 32 mA         |
| Voltage                      | 230 V         |
| Energy consumption           | 4 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Power factor                 | 0.5           |
| Useful luminous flux*        | 340 lm (360°) |
| Luminous flux**              | 340 lm (360°) |
| Lamp efficacy                | 85 lm/W       |
| Colour temperature           | 1800 K        |
| Colour of light              | WW            |
| Beam angle                   | 300 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | +40/-20 °     |
| Lifespan                     | 17000 h       |
| Socket                       | E14           |
| Degree of protection (IP)    | IP20          |
| Dimension (AxBxC)            | 35x98 mm      |
| Made in                      | PRC           |

## Related documents

---



 Declaration of Conformity

