

ALGINE BACKLIGHT 30W led panel 62x62 cm



Power	30 W	Voltage	230 V
Luminous flux*	4200 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
UGR	<19	Degree of protection (IP)	IP20



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI035062CW_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4200 lm (360°)
Luminous flux**	3300 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x32 mm
Weight	2 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	INT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux