

**LED R-50 6W E-14**



Power **6 W**  
Luminous flux\*\* **410 lm (360°)**  
Colour of light **WW**  
Socket **E-14**

Voltage **230 V**  
Colour temperature **3000 K**  
Beam angle **120 °**



 Declaration of Conformity



 Photometric file

**Technical data:**

|                              |               |
|------------------------------|---------------|
| Code                         | WOJ+13987     |
| Power                        | 6 W           |
| Nominal current              | 50 mA         |
| Voltage                      | 230 V         |
| Energy efficiency class      | G             |
| Energy consumption           | 6 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Power factor                 | 0.5           |
| Useful luminous flux*        | 420 lm (120°) |
| Luminous flux**              | 410 lm (360°) |
| Lamp efficacy                | 70 lm/W       |
| Luminous intensity           | 110 cd        |
| Colour temperature           | 3000 K        |
| Colour of light              | WW            |
| Beam angle                   | 120 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Socket                       | E-14          |
| Dimension (AxBxC)            | 50X82 mm      |
| Weight                       | 0.04 kg       |
| For use                      | Inside        |
| Application                  | INT           |
| Made in                      | PRC           |

