



---

|                 |                      |
|-----------------|----------------------|
| Power           | <b>10 W</b>          |
| Luminous flux** | <b>950 lm (360°)</b> |
| Colour of light | <b>WW</b>            |
| Socket          | <b>GU10</b>          |

---

|                    |               |
|--------------------|---------------|
| Voltage            | <b>230 V</b>  |
| Colour temperature | <b>3000 K</b> |
| Beam angle         | <b>20 °</b>   |

---



 Declaration of Conformity

**Technical data:**

|                              |                                   |
|------------------------------|-----------------------------------|
| Code                         | WOJ+14686                         |
| Power                        | 10 W                              |
| Nominal current              | 60 mA                             |
| Voltage                      | 230 V                             |
| Energy efficiency class      | F                                 |
| Energy consumption           | 10 kWh/1000h                      |
| Frequency                    | 50HZ Hz                           |
| Power factor                 | 0.7                               |
| Useful luminous flux*        | 750 lm (90°)                      |
| Luminous flux**              | 950 lm (360°)                     |
| Lamp efficacy                | 75 lm/W                           |
| Luminous intensity           | 1500 cd                           |
| Colour temperature           | 3000 K                            |
| Colour of light              | WW                                |
| Beam angle                   | 20 °                              |
| RA                           | 80                                |
| Uniformity of color SDCM max | 5                                 |
| Dimmable                     | Yes                               |
| Working temperature range    | -20/+40 °                         |
| Lifespan                     | 17000 h                           |
| Socket                       | GU10                              |
| Dimension (AxBxC)            | 111x74 mm                         |
| For use                      | Inside                            |
| Application                  | INT                               |
| Made in                      | PRC                               |
| Other                        | WOJ+06586; BERKER 2973, 296110; , |

