

PLATEO SUN 4

SLI044032NW_PW

High bay luminaire PLATEO SUN 4, with a power of 105 W, high light efficacy 110 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 70° gives directional light so that selected surfaces can be better exposed. Designed for suspended mounting.

IP65

IK06




Power	105 W	Voltage	230 V
Luminous flux*	11550 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	70 °
IK	06	Degree of protection (IP)	IP65

Technical data

Code	SLI044032NW_PW
Power	105 W
Nominal current	465 mA
Voltage	230 V
Energy consumption	105 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	11550 lm (360°)
Luminous flux**	10500 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	7800 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	70 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	Aluminum / PC
IK	06
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	218x80 mm
For use	Outside
Assembly method	Suspended
Application	Outside
Made in	PRC

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	420 pcs.
Gross weight (1 pcs.)	0.62 kg



Related documents

 User manual Declaration of Conformity

