Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			1013 With regard to energ	B) 1400 B o		
Supplier's name	e or trade mark:	McShine				
Supplier's address: Vertrieb, Schmalbachstrasse 16, 38112 Braunschweig, DE Model identifier: 1451332						
Lighting techno	logy used:	LED	Non-directional or directional:	DLS		
Light source cap	o-type	GU5.3				
(or other electric interface)						
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
		Product para				
Parameter		Value	Parameter	Value		
		General product		_		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		250 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), ex- pressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	50	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	50 50	range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,437		
		nates (x and y)	0,405		
Parameters for directional light sources:					
Peak luminous intensity (cd)	100	Beam angle in degrees, or the range of beam angles that can be set	100		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	4	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

