## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: McShine

Supplier's address: Vertrieb, Schmalbachstrasse 16, 38112 Braunschweig, DE

## Model identifier: 1451333

## Type of light source:

| Lighting technology used:     | LED   | Non-directional or directional: | DLS |  |  |
|-------------------------------|-------|---------------------------------|-----|--|--|
| Light source cap-type         | GU5.3 |                                 |     |  |  |
| (or other electric interface) |       |                                 |     |  |  |
| Mains or non-mains:           | NMLS  | Connected light source (CLS):   | No  |  |  |
| Colour-tuneable light source: | No    | Envelope:                       | -   |  |  |
| High luminance light source:  | No    |                                 |     |  |  |
| Anti-glare shield:            | No    | Dimmable:                       | No  |  |  |
| Product parameters            |       |                                 |     |  |  |

| Parameter                              |   | Value                      | Parameter  | Value        |  |  |
|--|---|----------------------------|--|--------------|--|--|
| General product parameters:            |   |                            |  |              |  |  |
|  | nption in on-<br>00 h), rounded<br>st integer                                   | 3                          | Energy efficiency<br>class   | F            |  |  |
| dicating if it refe<br>a sphere (360°) | s flux (φuse), in-<br>ers to the flux in<br>, in a wide cone<br>rrow cone (90º) | 250 in Wide<br>cone (120°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 4 000        |  |  |
| On-mode pow<br>pressed in W            | ver (P <sub>on</sub> ), ex-   | 3,0                        | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| (P <sub>net</sub> ) for CLS, e         | andby power<br>expressed in W<br>the second dec-                                | -                          | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |
| Outer dimen-                           | Height  | 50                         | Spectral power dis-  | See image    |  |  |
| sions without<br>separate con-         | Width<br>Depth  | 50<br>50                   | tribution in the range 250 nm to 800   | in last page |  |  |
| trol gear, light-<br>ing control       |   |                            | nm, at full-load   |              |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |   |                |  |  |  |
|--|------|---|----------------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W)  | -              |  |  |  |
|  |      | Chromaticity coordi-<br>nates (x and y)                                       | 0,380<br>0,380 |  |  |  |
| Parameters for directional light sources:                                  |      |   |                |  |  |  |
| Peak luminous intensity (cd)   | 100  | Beam angle in de-<br>grees, or the range<br>of beam angles that<br>can be set | 100            |  |  |  |
| Parameters for LED and OLED light sources:                                 |      |   |                |  |  |  |
| R9 colour rendering index value  | 4    | Survival factor   | 0,90           |  |  |  |
| the lumen maintenance factor   | 0,96 |   |                |  |  |  |

(a)'-' : not applicable;

(b)'-' : not applicable;

