Product Information Sheet

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: McShine Supplier's address: Vertrieb, Schmalbachstrasse 16, 38112 Braunschweig, DE Model identifier: 1451343											
							Type of light so	urce:			
							Lighting technology used:		LED	Non-directional or directional:	NDLS
							Light source cap-type		other		
(or other electric interface)											
Mains or non-m	ains:	NMLS	Connected light source (CLS):	No							
Colour-tuneable light source:		No	Envelope:	-							
High luminance light source:		No									
Anti-glare shield	d:	No	Dimmable:	No							
		Product para	meters								
Parameter		Value	Parameter	Value							
		General product p	arameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	F							
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		450 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000							
On-mode power (P _{on}), expressed in W		5,3	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00							
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80							
Outer dimen-	Height	9	Spectral power dis-	See image							

tribution

25

500

the

in

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,440			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

