Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	ELEGATED REGUL	LATION (EU) 2019/2	.015 with regard to ener	gy labelling of light	
Supplier's name	e or trade mark:	McShine			
Supplier's address: Vertrieb, Schmalbachstrasse 16, 38112 Braunschweig, DE					
Model identifie	er: 1451344				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type		other			
(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:		No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	No	
		Product para	T	Ι .	
Parameter		Value	Parameter	Value	
		General product p	T	_	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		450 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 200	
On-mode power (P _{on}), expressed in W		5,3	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	9	Spectral power dis-	See image	
sions without separate con- trol gear, light- ing control	Width Depth	25 500	tribution in the range 250 nm to 800 nm, at full-load	in last page	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,440			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

