Product Information Sheet

trol gear, light-

control

ing

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLEGATED REGOT	LATION (LO) 2013/20	ora with regard to energ	gy labelling of light
Supplier's name	e or trade mark:	McShine		
Supplier's addre	ess: Vertrieb, Sch	nmalbachstrasse 16,	38112 Braunschweig, D	ÞΕ
Model identifie	er: 1451413			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		G4		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para	T	
Parameter		Value	Parameter	Value
		General product p	T	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	G
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		112 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), ex- pressed in W		2,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without	Height	13	Spectral power dis-	See image
	Width	13	tribution in the	in last page
separate control gear, light-	Depth	27	range 250 nm to 800 nm, at full-load	

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,380			
		nates (x and y)	0,385			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

