Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: McShine						
Supplier's address: Vertrieb, Schmalbachstrasse 16, 38112 Braunschweig, DE						
Model identifier: 1451746						
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		G4				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
Product parameters Notice Product parameters						
Parameter		Value General product p	Parameter	Value		
Fnergy consur	nption in on-	3	Energy efficiency	G		
mode (kWh/1000 h), rounded up to the nearest integer		3	class	, ,		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		200 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), ex- pressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	35	Spectral power dis-	See image		
sions without	Width	35	tribution in the range 250 nm to 800	in last page		
separate con- trol gear, light- ing control	Depth	42	nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,463		
		nates (x and y)	0,420		
Parameters for directional light sources:					
Peak luminous intensity (cd)	170	Beam angle in degrees, or the range of beam angles that can be set	27		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	9	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

