Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: | SPECTRUM |
|--------------------------------|----------|
|--------------------------------|----------|

Supplier's address: Wojnarowscy, Gospodarcza 16 40-432 Katowice Poland

Model identifier: WOJ+22306_20W

| _ | • | | | |
|------|-----|-------|------|------|
| Type | Λt | light | COLL | rca. |
| IVDE | VI. | HEILL | SOU | LC. |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|-----|---------------------------------|------|
| Light source cap-type | G13 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| Product parameters | | | |

| Product parameters | | | | |
|---|---|---------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | | General product p | parameters: | |
| Energy consur mode (kWh/10 up to the neare | 00 h), rounded | 20 | Energy efficiency class | E |
| dicating if it refe a sphere (360º) | s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º) | 2 300 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 20,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 83 |
| Outer dimen- | Height | 1 500 | Spectral power dis- | See image |
| sions without | Width | 28 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 28 | range 250 nm to 800 nm, at full-load | |

| | 1 | | | |
|--|--|----------------------|-------|--|
| parts and non- | | | | |
| lighting con- | | | | |
| trol parts, if | | | | |
| | | | | |
| ' ' | | | | |
| tre) | | | | |
| Claim of equivalent power(a) | - | If yes, equivalent | - | |
| · | | power (W) | | |
| | | ` ` ` ′ | 0,436 | |
| | | Chromaticity coordi- | · · | |
| | | nates (x and y) | 0,402 | |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | 14 | Survival factor | 0,90 | |
| the lumen maintenance factor | 0,96 | | | |
| Parameters for LED and OLED m | Parameters for LED and OLED mains light sources: | | | |
| displacement factor (cos φ1) | 0,87 | Colour consistency | 5 | |
| | , | in McAdam ellipses | | |
| Claims that an LED light source | (b) | • | | |
| Claims that an LED light source | _(5) | If yes then replace- | - | |
| replaces a fluorescent light | | ment claim (W) | | |
| source without integrated bal- | | | | |
| last of a particular wattage. | | | | |
| | 0,1 | Stroboscopic offect | 0.1 | |
| Flicker metric (Pst LM) | 0,1 | Stroboscopic effect | 0,1 | |
| | | metric (SVM) | | |

(a)'-': not applicable; (b)'-': not applicable;

