Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: SPECTRUM |
|--|
| Supplier's address: Woingrowscy, Gospodarcza 16 40-432 Katowice Poland |

| Model identifier: WOJ+13133 | Model | identifier: | W∩I+13133 |
|-----------------------------|-------|-------------|-----------|
|-----------------------------|-------|-------------|-----------|

| Type of light source: | Type | of light | source: |
|-----------------------|------|----------|---------|
|-----------------------|------|----------|---------|

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

Height

Width

Depth

| Lighting technology used: | LED | Non-directional or directional: | DLS |
|--|----------------------------|--|-------|
| Light source cap-type | GU5.3 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| | Product para | meters | |
| Parameter | Value | Parameter | Value |
| General product parameters: | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | 6 | Energy efficiency class | F |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 480 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P _{on}), expressed in W | 6,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or | 82 |

50

50

50

the range of CRI-values that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in the

tribution

See image

in last page

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|--|--|-------|--|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 48 | | |
| | | Chromaticity coordi- | 0,436 | | |
| | | nates (x and y) | 0,402 | | |
| Parameters for directional light | sources: | | | | |
| Peak luminous intensity (cd) | 210 | Beam angle in degrees, or the range of beam angles that can be set | 110 | | |
| Parameters for LED and OLED lig | Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | 14 | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,96 | | | | |

(a)'-': not applicable; (b)'-': not applicable;

