## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: | SPECTRUM |
|--------------------------------|----------|
|--------------------------------|----------|

Supplier's address: Wojnarowscy, Gospodarcza 16 40-432 Katowice Poland

Model identifier: WOJ+11794

| Lighting technology used:     | LED | Non-directional or directional: | NDLS |  |
|-------------------------------|-----|---------------------------------|------|--|
| Light source cap-type         | E27 |                                 |      |  |
| (or other electric interface) |     |                                 |      |  |
| Mains or non-mains:           | MLS | Connected light source (CLS):   | No   |  |
| Colour-tuneable light source: | No  | Envelope:                       | -    |  |
| High luminance light source:  | No  |                                 |      |  |
| Anti-glare shield:            | No  | Dimmable:                       | No   |  |
|                               |     |                                 |      |  |

## **Product parameters**

| Froduct parameters                                |  |                        |  |              |  |  |
|---|--|------------------------|--|--------------|--|--|
| Parameter   |  | Value                  | Parameter  | Value        |  |  |
|   | General product parameters:  |                        |  |              |  |  |
| ٠,  | nption in on-<br>00 h), rounded<br>st integer                                    | 1                      | Energy efficiency<br>class   | G            |  |  |
| dicating if it refe<br>a sphere (360º)            | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>errow cone (90º) | 40 in Sphere<br>(360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 000        |  |  |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-  | 1,0                    | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| (P <sub>net</sub> ) for CLS, 6                    | candby power expressed in W the second dec-                                      | -                      | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 82           |  |  |
| Outer dimen-                                      | Height   | 70                     | Spectral power dis-  | See image    |  |  |
| sions without                                     | Width  | 45                     | tribution in the   | in last page |  |  |
| separate con-<br>trol gear, light-<br>ing control | Depth  | 45                     | range 250 nm to 800<br>nm, at full-load  |              |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-  |      |  |                |  |
|---|------|--|----------------|--|
| claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)           | -              |  |
|   |      | Chromaticity coordinates (x and y)     | 0,321<br>0,346 |  |
| Parameters for LED and OLED light sources:  |      |  |                |  |
| R9 colour rendering index value   | e 24 | Survival factor                        | 0,90           |  |
| the lumen maintenance factor  | 0,96 |  |                |  |
| Parameters for LED and OLED mains light sources:  |      |  |                |  |
| displacement factor (cos φ1)  | 0,90 | Colour consistency in McAdam ellipses  | 5              |  |
| Claims that an LED light source replaces a fluorescent ligh source without integrated bal last of a particular wattage. | t    | If yes then replace-<br>ment claim (W) | -              |  |
| Flicker metric (Pst LM)   | 0,2  | Stroboscopic effect metric (SVM)       | 1,7            |  |

(a)'-': not applicable; (b)'-': not applicable;

